

DGM 1035 (2380-185) Folder new in 2005

- 22 3/4" Cut-off
- Minimum 1/2 web of 30lb. newsprint at 32,000 PPH
- Maximum 10 webs of 30lb. newsprint at 25,000 PPH
- Delivery is fold first for 1/2 fold
- Closed head leading/spine to RTF side 1/4 fold
- Motorized conveyor press speed tracking and adjustable shingle.
- All products deliver to a common conveyor
- Web size: 1/2 and 1/4 fold a minimum 20" (508mm) full web or 10" (254mm) ribbon;
- 1/2 and 1/4 fold a maximum 36" (914mm); full web or 18" (457mm) ribbon
- Two sets of nips
- Lap Adjustment: Stop and move design Max. +/- .500" (12.7mm) by moving shims
- 56-degree former board, drilled for air, pneumatic trolleys and driven tabloid slitter
- Pin cylinder: 437" (11.09mm) pin hole to lead edge spacing, 12 pins across cylinder
- Jaw cylinder: single piece 2 around cylinder; torsion bar jaw spring & double track cam followers riding on side by side plate cams.
- Cam timing is adjustable from front of folder
- 1/4 folder: pecking type chopper assembly with tape transport system
- Safety guards



Optional Features included:

- 3rd set nipping rollers
- Triple under fold leads
- Upper former